INCH-POUND

MIL-STD-209K
22 February 2005
SUPERSEDING
MIL-STD-209J
28 January 1998

DEPARTMENT OF DEFENSE

INTERFACE STANDARD FOR LIFTING AND TIEDOWN PROVISIONS



AMSC N/A FSC 2540 DISTRIBUTION STATEMENT A. Approved for public release; Distribution is unlimited.

MIL-STD-209K

FOREWORD

- 1. This interface standard is approved for use by all Departments and Agencies of the Department of Defense.
- 2. This standard covers the design and testing of lifting, tiedown, and cargo tiedown provisions. The requirements in this standard are military-unique interface requirements developed specifically for ensuring that the lifting and tiedown provisions on military equipment meet the physical, functional and operational environment attributes for transportation assets of the Defense Transportation System (DTS). These requirements are necessary to permit the interoperability between transported military equipment and the transportation system available for military movements. Changes incorporated in this revision include the addition of a new type of provision to the standard, supplemental air transport tiedown provisions. This revision also redefines the definitions for the types of equipment that require provisions, and combines cargo bed tiedowns and flatbed/flatrack tiedowns into one type of provision that is simply called "cargo tiedown" provisions. Additionally, this revision of the standard has been reformatted so that it is easier to find the specific requirements for each type of provision covered under this standard.
- 3. The following service points of contact can provide assistance with questions concerning this military standard:
- U.S. Army SDDCTEA (for questions concerning interpretating this standard, and on highway, rail, and marine transport), dpemail@tea.army.mil, (757) 599-1109.
- U.S. Air Force ASC/ENFC (ATTLA) (for questions concerning transport on Air Force fixed wing aircraft), ATTLA@wpafb.af.mil, (937) 255-2330.
- U.S. Navy/Marine Corps (for questions concerning transport on Navy/Marine Corps aircraft), (301) 342-9392 (internal transport), (732) 323-2578 (external transport).
- U.S. Army Natick (for questions concerning Helicopter Sling Load (HSL) and internal transport on U.S. Army helicopters), (508) 233-5289.
- 4. Comments, suggestions, or questions on this document should be addressed to Director, Surface Deployment and Distribution Command Transportation Engineering Agency (SDDCTEA), ATTN: SDTE-DPE, 720 Thimble Shoals Blvd, Suite 130, Newport News, VA 23606-4537 or emailed to DPEmail@tea.army.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at http://assist.daps.dla.mil.

Table of Contents

1. SCOPE	. 1
1.1 Coverage	. 1
1.1.1 Excluded equipment	. 1
1.1.2 Military equipment for helicopter sling loading	. 1
1.1.3 Military equipment for airdrop	
1.2 Application	
1.3 Equipment types	
2. APPLICABLE DOCUMENTS	
2.1 Specifications and standards	2
2.2 Other Government documents, drawings, and publications	3
2.3 Order of precedence	3
3. DEFINITIONS	
3.1 Cargo tiedown provision	
3.2 Container spreader bar	3
3.3 Design limit load	
3.4 Equipment	4
3.5 Equipment tiedown provision	4
3.6 Gross weight (GW)	4
3.7 Gross Vehicle Weight Rating (GVWR)	4
3.8 Helicopter flight testing	
3.9 Helicopter sling loading (HSL)	. 4
3.10 Helicopter sling load weight (HSLWT)	4
3.11 Largo cargo tiedown provision	
3.12 Lifting provision	. 4
3.13 Multipurpose provision	5
3.14 Permanent deformation	. 5
3.15 Plane of the provisions	5
3.16 Static lift test	5
3.17 Static load	
3.18 Supplemental air transport tiedown provision	5
3.19 Ultimate load	5
3.20 Yield load	5
4. GENERAL REQUIREMENTS	
4.1 Restraint of Item	
4.2 Surface of provisions	
4.3 Shackles	
4.4 Hub and axle attachments	
4.5 Removable provisions.	6